



DIN 766

SIZE d mm		INSIDE LENGTH t			INSIDE WIDTH b1	OUTSIDE WIDTH b2	LENGTH PER 11 LINKS			WEIGHT PER M
mm	± mm	mm	+ mm	- mm	mm	mm	mm	+ mm	- mm	kg
3	0.2	14.5	0.2	0.2	4.5	11	159.5	1.4	0.7	0.16
4	0.2	16	0.3	0.2	5	13.7	176	2.1	1.1	1.32
5	0.2	18.5	0.4	0.2	6	17	203.5	2.4	1.2	0.5
6	0.2	18.5	0.4	0.2	7.2	20.2	203.5	2.4	1.2	0.8
7	0.3	22	0.4	0.2	8.4	23.8	242	3.0	1.4	1.1
8	0.3	24	0.4	0.2	9.6	27.2	264	3.2	1.5	1.4
9	0.4	27	0.5	0.3	10.8	30.6	297	3.6	1.8	1.8
10	0.4	28	0.5	0.3	12	34	308	3.7	1.9	2.2
11	0.4	31	0.5	0.3	13.2	37.4	341	4.0	2.0	2.7
12	0.3	36	0.6	0.3	14.4	40.8	396	4.4	2.2	3.1
13	0.5	36	0.6	0.3	15.6	44.2	396	4.6	2.4	3.8
14	0.6	41	0.7	0.4	16.8	47.6	451	5.4	2.7	4.4
16	0.6	45	0.8	0.4	19.2	54.4	495	6.0	3.0	5.7
18	0.9	50	0.8	0.4	21.6	61.2	550	6.6	3.3	7.3
19	0.4	53	0.9	0.4	22.8	64.4	583	7.0	3.7	7.97
20	1.0	56	1.0	0.5	24.0	68.0	616	7.4	3.7	9
23	1.2	64	1.1	0.5	27.6	78.2	704	8.4	4.2	12
26	1.3	73	1.2	0.6	31.2	88.4	803	9.6	4.8	15
28	1.4	78	1.3	0.65	33.8	95.2	858	10.2	5.1	18
30	1.5	84	1.4	0.7	41	102	924	11.0	5.5	19.5
32	1.6	90	1.5	0.75	43	108.8	990	11.8	5.9	23.0